



Electronic pipette controller

CODE - MBD002

- Intuitive and convenient speed with 6 levels
- Lightweight pipette filler compatible with glass or plastic serological pipettes (0.1-100 mL)
- Ergonomic design for fatigue-free and effective streamlined pipetting
- LCD screen displays battery status and pipetting speed
- Quiet and powerful motor and pup fills 25 mL pipette in less than 5 seconds
- Long-lasting lithium-ion battery

FAVS
Scientific Equipment
di Gnudi Andrea e Antonella S.r.l.
Tel. 051501153
www.favs.it • info@favs.it



LCD DISPLAY

Select pipetting speed by pressing
+/- button

SELECTORS

Selección de la velocidad de
pipeteo con los botones +/-

BUTTON

Operating button for motor
and gravity dispensing



Hydrophobic filter
0.45µm



CODE - MBG015
Silicone adapter



CODE - MBG014
Tapered nozzle

Technical specifications

Code	MBD002
Aspiration speed	25mL<5s (6 levels)
Dispensing Speed	Motor (6 shift) / Gravity
Battery	Lithium-ion
Battery Service Life	More than 8 hours of untermittent use
Tiempo de carga	2-3 hours
Pipette Types	Glass or Plastic Pipette (0.1-100mL), Pasteur Pipettes
Filter	0.45 µm hydrophobic
Height	200 g