



FAVS
Scientific Equipment

Tel. 051501153
www.favs.it • info@favs.it

Inverted LED brightfield metallurgical microscope, 500x, IOS LWD PLAN MET

Observation Method - Incident Light	Brightfield	Yes
	Simple polarized light	Yes
Main Body	Type	Inverted
	Construction material	Aluminum die-cast
	Trasportation handle	Yes
Head	Type	Trinocular (Siedentopf)
	Split ratio	100/0 - 50/50
	Inclination	45°
	Interpupillary distance (mm)	50-75
	Diopter adjustment	On left tube
	Fixing screw for eyepieces	No
	Tube inner diameter (mm)	30
Eyepieces	Field number (mm)	22
	Magnification	10x
	Planar type	Yes
	Micrometric scale	As optional
	Diameter of micrometer glass (mm)	26
	High eyepoint (for glass wearers)	Yes
	Rubber cup	Yes
	Retractable protections	Yes
Nosepiece	Positions	Quintuple
	Reversed	Yes
	Bi-directional	Yes
	Rotation on ball bearings	Yes
	Objective thread	RMS
Objectives	Optical system	∞
	Anti-fungus treatment	Yes
	Parfocal distance (mm)	45
	Standard magnifications	50x-500x
	Type	IOS LWD U-PLAN MET
		IOS LWD U-PLAN MET 5x/0.15, W.D. 10.8 mm
		IOS LWD U-PLAN MET 10x/0.30, W.D. 10.0 mm

		IOS LWD U-PLAN MET 20x/0.45, W.D. 4.0 mm
		IOS LWD U-PLAN MET 50x/0.55, W.D. 7.9 mm

Stage	Type	Fixed
	Dimensions (mm)	250x160
	Material	Anti-scratch painting
	Metal round insert	Yes

Focusing System	Type	Coaxial coarse & fine
	Focus modes	Coarse & fine
	Fine graduations	100
	Fine total travel (per single rotation) (mm)	0.2
	Fine resolution (µm)	2
	Adjustable tension	Yes

Accessories Included	Dust cover	Yes
	Allen wrench	Yes
	Green filter	Yes
	LBD filter	Yes
	User Manual	Digital version (downloadable)

Additional Information		Mechanical stage dimension 250x230 mm, X-Y translation range 120x80 mm (as optional).
-------------------------------	--	---

Product Dimensions	Height (mm)	390
	Width (mm)	230
	Depth (mm)	600

Product Weight	(kg)	8.8
-----------------------	------	-----

Metallographic Light Source	Light source	LED
	Light source power (W)	18
	Lifetime (hours)	> 65,000
	Temperature (K)	4,000
	Brightness control	Yes

Metallographic Power Supply	Type	External
	Microscope connector	Jack, 2.1 mm
	Power plug type	European
	Input voltage	110/240 Vac, 50/60 Hz
	Output Voltage	24 Vdc 2,5 A