



# ES

## Overhead Stirrers

---

Overhead stirrer for low viscosity liquids



# Resistant and Easy-to-Use

The ES is an intuitive overhead stirrer ensuring safety with overload, over-current and overheating protection.

- Maximum torque of 15 Ncm
- Supports applications with a maximum viscosity of 1000 mPa\*s
- Electronic speed regulation from 50 to 1300 rpm, up to 15 L
- Long life, robust motor
- Easy-chuck to change the shafts without tools
- Automatically stops if blocked – no burn-out or damage
- Overload, overcurrent and overtemperature protection
- Sealed to IP 40 standard



## INSTRUMENT - CODE

ES

110-230 V / 50-60 Hz

F201A0152

## TECHNICAL DATA

CONSTRUCTION MATERIAL	Technopolymer and epoxy painted aluminum alloy
CHUCK RANGE	1 - 10 mm
ELECTRONIC PROTECTION RATING CEI EN 60529	IP 40
ELECTRONIC SPEED REGULATION	From 50 to 1300 rpm
STIRRING VOLUME MAX (H <sub>2</sub> O)	Up to 15 L
MAX VISCOSITY	1000 (mPa*s)*
TORQUE MAX	15 Ncm
ALLOWED ROOM TEMPERATURE	From 0 to 40 °C
DIMENSION (WXHXD)	80x160x200 mm (3.1x6.3x7.9 in)
POWER	30 W
WEIGHT	1.3 Kg (2.8 lb)



We reserve the right to make technical alterations  
We do not assume liability for errors in printing, typing or transmission

**favs**  
Scientific Equipment

Tel. 051 501153 - Fax 051 6336182  
[www.favs.it](http://www.favs.it) - [info@favs.it](mailto:info@favs.it)

DESIGNED AND MANUFACTURED IN ITALY

**VELP**  
SCIENTIFICA

**ITALY - HQ**  
Via Stazione 16  
20865 Usmate (MB) Italy  
Tel. +39 039 628811  
[velpitalia@velp.com](mailto:velpitalia@velp.com)

**INDIA**  
[velpindia@velp.com](mailto:velpindia@velp.com)

**USA**  
155 Keyland Court, Bohemia  
NY 11716 - U.S.  
Tel. +1 631 573 6002  
[velpusa@velp.com](mailto:velpusa@velp.com)

**CHINA**  
Xinlong Rd Building 28, Lane 1333  
Shanghai city - China  
Tel. +86 180 1755 7329  
[velpchina@velp.com](mailto:velpchina@velp.com)