

AMI Series

Magnetic Stirrers

Single-position or 4-position illuminated magnetic stirrer, particularly indicated for titrations



Resistant and Easy-to-use

Illuminated magnetic stirrer particularly useful for titrations. The illuminated surface facilitates the visualization of particles and color changes. It guarantees excellent speed control (electronic), even at low speed.

- Speed regulation up to 1100 rpm
- Excellent electronic speed control, even at low speed





INSTRUMENT - CODE

AMI	100-240 V / 50-60 Hz	F204A0167
AMI 4	100-240 V / 50-60 Hz	F204A0168

TECHNICAL DATA

	АМІ	AMI 4
CONSTRUCTION MATERIAL	Epoxy painted metal structure	Epoxy painted metal structure
MODELS	Single-position	4-position
STIRRING VOLUME	up to 5 L	up to 5 L
DISTANCE BETWEEN STIRRING POSITION CENTRES	-	150 mm
ELECTRONIC SPEED REGULATION	Up to 1100 rpm	Up to 1100 rpm
SPEED CONTROL	Excellent speed control even at low revolutions	Excellent speed control even at low revolutions
STIRRING SYSTEM	High-power driving magnet type "PCM" operated by a mono-phase motor for continuous operation	High-power driving magnet type "PCM" operated by a mono-phase motor for continuous operation
DIMENSION (WXHXD)	150x55x270 mm (5.9x2.2x10.6 in)	600x55x270 mm (23.6x2.2x10.6 in)
POWER	1.2 W	4.8 W
WEIGHT	1.2 Kg (2.6 lb)	4.0 Kg (8.8 lb)




















ITALY - HQ Via Stazione 16 20865 Usmate (MB) Italy Tel. +39 039 628811 velpitalia@velp.com

INDIA

velpindia@velp.com

DESIGNED AND MANUFACTURED IN ITALY

155 Keyland Court, Bohemia Tel. +1 631 573 6002 velpusa@velp.com

CHINA

Xinlong Rd Building 28, Lane 1333 Shanghai city - China Tel. +86 180 1755 7329 velpchina@velp.com