


# Hotplate

digital, up to 380°C, ceramic-coated plate



## HP-D digital, 380°C

### Ideal for:

- sample drying and general lab heating applications

### Features:

- up to 380°C
- digital display with backlight
- ceramic-coated aluminium plate 180x180 / 260x260 mm
- heat-, chemical- and restricted acid-resistant
- powder-coated body
- CE certified and unique serial number for tracing

### Safety mechanism:

- timer 99h 59min with timer-end signal
- error status
- locking mode
- operation LEDs

### Controller:

- **Jog-Shuttle** controller with touch-button



HP-30D



HP-20D Set

Model	HP-20D	HP-30D
Body	powder-coated aluminium	powder-coated steel
Plate	ceramic-coated aluminium 180x180 mm	ceramic-coated aluminium 260x260 mm
Temperature range & accuracy	max. 380°C, ±0.3°C	
Temperature resolution	0.1°C display, 0.5°C control	
Temperature uniformity	specially designed heating module: temperature difference less than 10%	
Heating power / consumption	600W	1.2kW
Timer & alarm	99h 59min (with continuous run), error status and timer-end	
Display	digital LCD with backlight function	
Controller	digital feedback controller with Jog-Dial (Turn+Push) and touch-button	
Safety circuit	overheat protection	
Permissible temperature & RH %	ambient temperature +5 ~ 50°C, 85% RH	
Dimension & weight	206x307xh99 mm, 2.8 kg	286x387xh99 mm, 3.2 kg
Packaging size	400x280xh200 mm, 5 kg	430x320xh200 mm, 5 kg
Power supply	1 Phase AC 120V, 60 Hz or AC 230V, 50/60 Hz	
Order number 230V	Unit: DH.WHP03020   Set: DH.WHP03021	Unit: DH.WHP03022   Set: DH.WHP03023
Order number 120V	Unit: DH.WHP02020   Set: DH.WHP02021	Unit: DH.WHP02022   Set: DH.WHP02023

Set includes: Unit HP-D  
Temperature probe Ø4xL250 mm, cable length: 190 mm  
Stand rod Ø12xL450 mm, stainless steel (stand rod for HP-20D with thread)  
Holder / clamp / clip for fixation of temperature probe